

## STORYWALL CORK WALL TILES

### TECHNICAL SPECIFICATION

<b>GENERAL DEFINITION AND PRODUCT COMPOSITION</b>		
Definition		Solid agglomerated cork tiles, digitally printed, to be used as wallcoverings within buildings, contributing significantly to the acoustic and thermal performance of buildings, improving environmental comfort and reducing energy costs. The surface is fine sanded, printed and finished with a waterbased protector for increased water and stain resistance.
Dimensions		300 x 300 x 4 mm
Product structure and materials		Agglomerated cork; Waterbased paint; Inkjet digital print; CORKGUARD <sup>®</sup> Aqueous dispersion.
Installation system		Glued
<b>TECHNICAL DATA</b>		
Length and width	EN ISO 24342	300 x 300 mm ± 0.4 %
Overall thickness	ISO 7322	4 mm ± 0.2 mm
Squareness Straightness	EN ISO 24342	< 0.4 mm < 0.3 mm
Apparent density	ISO 7322	330 Kg/m <sup>3</sup>
Mass per unit area	EN ISO 23997	1300 g/m <sup>2</sup> ± 10 %
Tensile strength	ISO 7322	> 1000 kPa
Compression Recuperation	ISO 7322	< 40 % > 75 %
Dimensional variation	EN ISO 23999	< 0.4 %
Moisture content	EN 12105	< 8 %
Curling	EN ISO 23999	< 6 mm
Reaction to fire	EN 13501-1	Fire class E
Formaldehyde emission	EN 12149	Below Detection Limit No formaldehyde-containing products are added during the manufacturing.

## STORYWALL CORK WALL TILES

### TECHNICAL SPECIFICATION

TECHNICAL DATA		
Heavy metals and specific elements Arsenic; Barium; Cadmium; Chromium; Mercury; Lead; Antimony; Selenium	EN 12149	Fulfilled None of these substances are added or have come in direct contact with the product during the manufacturing process
Release of vinyl chloride monomer	EN 12149	Fulfilled. Below Detection Limit
Thermal resistance Thermal conductivity	EN 12667	0.07 (m <sup>2</sup> .K)/W 0.05 W/(m.K)
Sound absorption	ISO 354	Weighted sound absorption coefficient $\alpha_w = 0.05$
GENERAL DATA		
Features	<p>Safe and easy to handle and install; Effective reduction of airborne sound; Increases the thermal comfort; Persistence of characteristics along time; Without the release of toxic gases when burning; Lightweight, flexible and odourless; No harmful chemicals; Natural, biodegradable and recyclable product;</p>	
Packaging	<p>STORYWALL tiles are packed in cardboard cartons, each containing 88 tiles, providing suitable protection for normal transport and storage conditions. Cartons are identified by a label and/or inkjet printing and palletized. Each pallet is over strapped and wrapped with stretch film.</p> <p>Tiles per carton: 88 Sqm per carton: 7.92 m<sup>2</sup> Weight per carton: 11 Kg Cartons per pallet: 54 Sqm per pallet: 427.7 m<sup>2</sup></p>	
Lifetime limited warranty	<p>We certify that the product is free from manufacturing and structural defects and will remain free of these defects.</p>	
Environment	<p>The use of a natural and renewable raw-material and the possibility of total recycling of the product, make STORYWALL a reference in terms of ecology and environmental sustainability. STORYWALL tiles are made using more than 90% cork, which is a renewable raw material. It contains no PVC and no softeners or other substances hazardous to health or the environment.</p>	



EN 15102:2011

GRANORTE reserves the right to make changes to material and structure to improve the quality or technical performance.